

ZEFIRO PLUS

Monosplit Cassette Inverter
Heat pump

WISNOW

UNIT INDOOR		ZEFIRO PLUS 35 12000btu	ZEFIRO PLUS 53 18000btu	ZEFIRO PLUS 70 24000btu	ZEFIRO PLUS 105 36000btu	ZEFIRO PLUS 105 36000btu TRIF.	ZEFIRO PLUS 140 48000btu TRIF.	ZEFIRO PLUS 165 58000btu TRIF.
Air flow min / nom / max	m ³ / h	450/528/648	498/648/798	1032/1200/1378	1438/1620/1775	1438/1620/1775	1381/1568/1715	1537/1737/1970
Sound pressure level (H / M / L)	dB (A)	41/37/33	46/41/37	47/43/40	52/49/46	52/49/46	52/50/49	56/52/49
Sound power level (Max)	dB (A)	58	57	60	63	63	65	65
Dimensions (L × P × H)	mm	570x570x260	570x570x260	840x840x205	840x840x205	840x840x205	840x840x205	840x840x205
Packing dimensions	mm	655x655x290	655x655x290	900x900x225	900x900x225	900x900x225	900x900x225	900x900x225
Net weight	kg	16	16	23	27,5	27,5	29	29,7
Gross weight	kg	19	19	27	31	31	32,7	33,4
Panel dimensions (L × P × H)	mm	647x647x50	647x647x50	950x950x55	950x950x55	950x950x55	950x950x55	950x950x55
Net weight Panel	kg	2,5	2,5	5	5	5	5	5
Packing dimensions Panel (L × P × H)	mm	715x715x123	715x715x123	1035x1035x90	1035x1035x90	1035x1035x90	1035x1035x90	1035x1035x90
Net weight Packaging Panel	kg	4,5	4,5	8	8	8	8	8

UNIT OUTDOOR		ZEFIRO PLUS 35 12000btu	ZEFIRO PLUS 53 18000btu	ZEFIRO PLUS 70 24000btu	ZEFIRO PLUS 105 36000btu	ZEFIRO PLUS 105 36000btu TRIF.	ZEFIRO PLUS 140 48000btu TRIF.	ZEFIRO PLUS 165 58000btu TRIF.
Dimensions (L × P × H)	mm	800x333x555	800x333x554	845x363x702	946x410x810	946x410x810	952x410x1333	952x410x1333
Packaging dimensions (L × P × H)	mm	920x390x615	920x390x615	965x395x765	1090x500x875	1090x500x875	1095x495x1480	1095x495x1480
Net weight	kg	34,5	35,6	66,8	66,8	81,5	106,7	111,3
Gross weight	kg	37,3	38,5	72,6	73,4	87,0	119,9	124,3
Air flow rate	m ³ /min.	1998	2100	2700	4000	4000	7500	7500
Compressor		ROTATIVO	ROTATIVO	ROTATIVO	ROTATIVO	ROTATIVO	ROTATIVO	ROTATIVO
Refrigerant - Precharge Kg - GWP		R32/1,35/675	R32/1,35/675	R32/1,50/675	R32/2,40/675	R32/2,40/675	R32/2,8/675	R32/2,95/675
Liquid-Gas folder coupling		1/4"-3/8"	1/4"-1/2"	3/8"-5/8"	3/8"-5/8"	3/8"-5/8"	3/8"-5/8"	3/8"-5/8"
Length Piping Covered by preloading	m	5	5	5	5	5	5	5
Recommended minimum length of piping	m	3	3	3	3	3	3	3
Length Equivalent piping max	m	25	25	50	65	65	65	65
Maximum height difference	m	10	10	25	30	30	30	30
Supply		220-240V 50Hz	220-240V 50Hz	220-240V 50Hz	220-240V 50Hz	380-415V 50Hz	380-415V 50Hz	380-415V 50Hz
Maximum absorbed electrical power	W	2000	2100	2950	4700	5600	6200	7500
Maximum current	A	9,0	10,0	13,5	21,5	10,0	11,2	14,0

VUOI SCOPRIRE LA TUA ZONA CLIMATICA

E CALCOLARE IL TUO

CONTO TERMICO 2.0

VISITA IL NOSTRO SITO

www.wisnowitalia.it/incentivi-fiscali

