





# VISION

Monosplit Wall Inverter  
Heat pump

INTERNAL UNIT		VISON 9000btu	VISON 12000btu
Air flow rate Cold / warm	m <sup>3</sup> / h	<b>850 / 850</b>	<b>850 / 850</b>
Sound pressure level (H / M / L / Mute)	dB (A)	<b>43 / 38 / 27 / 18</b>	<b>43 / 38 / 27 / 18</b>
Sound power level (S / H / M / L / Mute)	dB (A)	53/49/45/37/34	53/49/45/37/34
Dimensions (L x H x P)	mm	<b>883x310x195</b>	<b>883x310x195</b>
Packing dimensions	mm	964x375x262	964x375x262
Net weight	kg	10,5	10,5
Gross weight	kg	13	13
Supply	Lt / h	1,0	1,2
EXTERNAL UNIT		GOLD PLUS 2.0 9000btu	GOLD PLUS 2.0 12000btu
Sound pressure level	dB (A)	52	52
Sound power level	dB (A)	62	62
Operating interval (Cold) min-max	° C	<b>-15° / +53°</b>	<b>-15° / +53°</b>
Operating interval (Hot) min-max	° C	<b>-20° / +30°</b>	<b>-20° / +30°</b>
Dimensions (L x H x P)	mm	795x305x549	795x305x549
Packaging dimensions (L x H x P) without connections	mm	835x340x585	835x340x585
Packing dimensions (W x H x D) with connections	mm	835x340x585	835x340x585
Net weight	kg	25	28
Gross weight	kg	28	28
Compressor		Rotativo	Rotativo
Refrigerant - Precharge Kg - TCO2Eq - GWP / CO2		<b>R32/0.56kg/675</b>	<b>R32/0.8kg/675</b>
CO2 Tonnes equivalent		0,378	0,54
Liquid-Gas folder coupling		1/4"-3/8"	1/4"-3/8"
Maximum linear length of the pipes	m	25	25
Maximum height difference	m	10	10
Selectable temperatures min.-max	° C	16-31	16-31
Supply		220-240V~/50hZ/1P	220-240V~/50hZ/1P
Voltage range	V	165~265	165~265
Operating current Cold	A	3.8(1.2~6.5)	5.4(1.2~7.2)
Operating current Hot	A	3.7(1.2~7.0)	4.5(1.2~8.0)
<b>Conto Termico</b>			

YOU WANT TO DISCOVER YOUR CLIMATE AREA

AND CALCULATE YOUR

**CONTO TERMICO 2.0**

VISIT OUR WEBSITE

**[www.wisnowitalia.it/incentivi-fiscali](http://www.wisnowitalia.it/incentivi-fiscali)**

